Canon

Canon imageFORMULA ScanFront 400 ADF scanner 600 x 600 DPI A4 Black, White

Brand : Canon

Product family: imageFORMULA

Article code: 1255C003

Product name : ScanFront 400

Canon imageFORMULA ScanFront 400. Maximum scan size: 216 x 356 mm, Optical scanning resolution: 600 x 600 DPI, ADF scan speed (b/w, A4): 45 ppm. Scanner type: ADF scanner, Product color: Black, White, Display: TFT. Sensor type: CMOS CIS, Daily duty cycle (max): 6000 pages, Light source: RGB LED. Auto document feeder (ADF) input capacity: 60 sheets. Maximum ISO A-series paper size: A4, Scanning media types supported: Business Card, Plastic Card, Post Card(JPN), ISO A-series sizes (A0...A9): A4

Scanning

Maximum scan size *	216 x 356 mm
Optical scanning resolution *	600 x 600 DPI
Color scanning	✔
Duplex scanning *	✔
Grayscale levels	256
ADF scan speed (b/w, A4)	45 ppm
ADF scan speed (color, A4)	45 ppm

Design

Scanner type *	ADF scanner
Product color *	Black, White
Display	TFT
Display diagonal	25,6 cm (10.1")
Display resolution	1024 x 600 pixels
Touchscreen	✔
Built-in display *	✔

Performance

Sensor type *	CMOS CIS
Light source	RGB LED
Scan file formats	PDF, PNG, TIFF
Daily duty cycle (max) *	6000 pages
Scan to	E-mail, FTP, Fax, USB

Input capacity

Auto document feeder (ADF) input capacity	60 sheets

Paper handling

Scanning media types supported	Business Card, Plastic Card, Post Card(JPN)
Maximum ISO A-series paper size *	A4
ISO A-series sizes (A0...A9)	A4
Media thickness (min)	0,04 mm

Paper handling

Auto Document Feeder (ADF) media weight	27 - 209 g/m²
Maximum scan width	21,6 cm
Maximum scan length	35,6 cm

Ports & interfaces

USB port *	✔
USB version	2.0
Standard interfaces	Ethernet, USB 2.0

Network

Ethernet LAN	✔
Supported network protocols	TCP/IP (IPv4), DNS, DHCP, SMB, NTP, HTTP, FTP, SFTP, Secure sending (FTPS and SMTPS), WebDAV, LDAPS

Power

Power supply type *	AC
Power consumption (typical)	40 W
Power consumption (off)	0,5 W
AC input frequency	50 - 60 Hz
Input voltage	100-240 V

Weight & dimensions

Width	305 mm
Depth	282 mm
Height	230 mm
Weight	4,5 kg

Sustainability

Sustainability certificates	ENERGY STAR

Operational conditions

Operating temperature (T-T)	10 - 32,5 °C
Operating relative humidity (H-H)	20 - 80%

Other features

Compliance certificates	RoHS

Technical details	
Panel type	TFT
Logistics data	
Harmonized System (HS) code	84716070

4528472107110

Catalog Object Cloud