Canon

Canon imageFORMULA DR-C225 II ADF + Manual feed scanner 600 x 600 DPI A4 Black

Brand : Canon Product family: Article code: 3258C003 imageFORMULA

illiagei OKMOL

Product name: DR-C225 II

Canon imageFORMULA DR-C225 II. Maximum scan size: 216×356 mm, Optical scanning resolution: 600×600 DPI, ADF scan speed (b/w, A4): 25 ppm. Scanner type: ADF + Manual feed scanner, Product color: Black. Sensor type: CMOS CIS, Daily duty cycle (max): 1500 pages, Light source: RGB LED. Maximum ISO A-series paper size: A4. Standard interfaces: USB 2.0





| Scanning | | Power | |
|--|---|--|--|
| Maximum scan size * Optical scanning resolution * Color scanning Duplex scanning * ADF scan speed (b/w, A4) ADF scan speed (color, A4) Duplex ADF scan speed (b/w, A4) Duplex ADF scan speed (color, A4) Duplex ADF scan speed (color, A4) | 216 x 356 mm 600 x 600 DPI 25 ppm 25 ppm 50 ipm 50 ipm | Power consumption (typical) Power consumption (off) AC input frequency Input voltage Power consumption (sleep) | 12,7 W 0,5 W 50 - 60 Hz 100-240 V 1,8 W |
| | | Weight & dimensions Width Depth Height | 300 mm 156 mm 220 mm |
| Scanner type * | ADF + Manual feed scanner | Weight | 2,8 kg |
| Product color * | Black | Packaging content | |
| Built-in display * Performance | × | Cables included Quick start guide | AC, USB ✓ |
| Sensor type * | CMOS CIS | AC adapter included | ✓ |
| Light source | RGB LED | Sustainability | |
| Daily duty cycle (max) * Scan drivers | 1500 pages ISIS, TWAIN | Sustainability certificates | ENERGY STAR |
| Scanner error detection | ✓ | System requirements | |
| Ultrasonic double sheet detection | ✓ | Windows operating systems supported | Windows 10, Windows 2000, Windows 7, Windows 8, Windows Vista, Windows XP Home, Windows XP Home x64, Windows XP Professional, Windows XP Professional x64 |
| Paper handling Maximum ISO A-series paper size * | A4 | | |
| Ports & interfaces | | Mac operating systems supported | ✓ |
| USB port * | ✓ | Mobile operating systems supported | Android, iOS |
| USB version Standard interfaces | 2.0 USB 2.0 | Operational conditions | |
| Power | | Operating temperature (T-T) Operating relative humidity (H-H) | 10 - 32,5 °C 20 - 80% |
| Power supply type * | AC | Other features | |
| | | Compliance certificates | RoHS |
| | | Logistics data | |
| | | Harmonized System (HS) code | 84716070 |





4528472108384

5415247303954

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.