

HP LaserJet Pro MFP 3103fdn Printer Laser A4 1200 x 1200 DPI 33 ppm

Brand : HP

Product family: LaserJet Pro

Article code: 3G631A

Product name : LaserJet Pro MFP 3103fdn Printer

HP LaserJet Pro MFP 3103fdn Printer. Print technology: Laser, Printing: Mono printing, Maximum resolution: 1200 x 1200 DPI. Copying: Mono copying, Maximum copy resolution: 300 x 300 DPI. Scanning: Colour scanning, Optical scanning resolution: 1200 x 1200 DPI. Duplex functions: Print, Copy. Maximum ISO A-series paper size: A4. Direct printing. Product color: Grey, White





Printing

| Duplex printing mode |
|--|
| Print resolution black |
| Print technology * |
| Printing * |
| Duplex printing * |
| Maximum resolution * |
| Print speed (black, normal quality, A4/US Letter) * |
| Warm-up time |
| Secure printing |
| |

Copying

Duplex copying * 1 Copying * Maximum copy resolution * Time to first copy (black, normal) Maximum number of copies Copier resize Auto fit function 1

Scanning

Duplex scanning * Scanning * Optical scanning resolution * Optical scanning resolution (black) Optical scanning resolution (colour) Optical scanning resolution (ADF) Maximum scan area Scanner type * Scan technology Scan to Scan speed (colour)

Auto 1200 x 1200 DPI Laser Mono printing 1200 x 1200 DPI 33 ppm

35 s

1

Mono copying 300 x 300 DPI 6.2 s 999 copies 25 - 400%

×

Colour scanning 1200 x 1200 DPI 1200 x 1200 ppi 1200 x 1200 ppi 300 x 300 DPI 216 x 297 mm Flatbed & ADF scanner CIS TWAIN, Software 8 ppm

| Ports & interfaces | |
|--|--------------------------------------|
| USB port | 1 |
| Network | |
| Wi-Fi * | x |
| Ethernet LAN * | ✓ |
| Cabling technology | 10/100Base-T(X) |
| Ethernet LAN data rates | 10,100 Mbit/s |
| Mobile printing technologies | Apple AirPrint, Mopria Print Service |
| Performance | |
| Maximum internal memory | 512 MB |
| Internal memory * | 512 MB |
| Built-in processor Processor frequency | ✓ 800 MHz |
| Sound pressure level (printing) | 53 dB |
| Sound power level (printing) | 6.6 dB |
| Design | |
| Product colour * | Grey, White |
| Market positioning * | Business |
| Built-in display * | 1 |
| Display | CGD |
| Display diagonal | 6.86 cm (2.7") |
| Control type | Touch |
| Colour display | • |
| Power | |
| Power consumption (PowerSave) | 0.06 W |
| Power consumption (printing) | 436 W 4.5 W |
| Power consumption (ready) Power consumption (sleep) | 4.5 W 1.31 W |
| Power consumption (siccp) | 0.06 W |
| • • • • | |

| Scanning | | Power | |
|---|---|--|--|
| Scan speed (black) | 19 ppm | Energy Star Typical Electricity Consumption (TEC) | 0.407 kWh/week |
| Image formats supported | JPG, TIFF | AC input voltage | 110 - 240 V |
| Document formats supported Input colour depth | PDF, XPS 24 bit | AC input frequency | 50/60 Hz |
| Greyscale levels | 256 | System requirements | |
| Scan drivers | TWAIN | Windows operating systems | |
| Fax | | supported | Windows 11, Windows 10 |
| Faxing * | × | Mac operating systems supported | Mac OS X 11.0 Big Sur, Mac OS X 12.0 Monterey, Mac OS X 10.15 |
| Fax resolution (black) | 300 x 300 DPI | Mac operating systems supported | Catalina |
| Fax transmission speed | 3 sec/page | Other operating systems supported | Linux |
| Modem speed | 33.6 Kbit/s | Operational conditions | |
| Fax memory | 500 pages | Operating relative humidity (H-H) | 10 - 80% |
| Auto-redialing | ✓ | Recommended humidity operating | 30 - 70% |
| Speed dialling | ✓ | range Operating temperature (T-T) | 15 - 32.5 °C |
| Fax forwarding | Image: A start of the start of | | 13-52.5 C |
| Fax delayed sending | | Certificates | |
| Auto reduction | √ | | CISPR32:2012 & CISPR32:2015 /EN55032:2012 & |
| Features | | Certification | EN55032:2015+AC:2016 - Class B; |
| Recommended duty cycle | 350 - 2500 pages per month | Certification | EN 61000-3-2:2014; EN 61000-3-3:2013; EN 55035:2017; |
| Maximum duty cycle * | 50000 pages per month | | FCC Title 47 CFR, Part 15 Class B/ICES-003, Issue 6 |
| Duplex functions * Number of print cartridges * | Print, Copy 1 | | Brices-005, issue 0 |
| Printing colours * | 1 Black | Sustainability | |
| Page description languages | PCL 5c, PCL 6, URF, PWG, PCLmS, | Sustainability compliance | |
| | PCLm, PDF | Sustainability certificates Doesn't contain | Blue Angel Mercury |
| Printer fonts | Scalable, TrueType | | Mercury |
| All-In-One-multitasking | ✓ Vietnam | Weight & dimensions | 410 |
| Country of origin HP segment | Small medium business | Width Depth | 418 mm 398.2 mm |
| | | Height | 313.2 mm |
| Input & output capacity Total number of input trays * | 1 | Weight | 10.5 kg |
| Total input capacity * | 1 250 sheets | Packaging data | |
| Total output capacity * | 150 sheets | Package width | 497 mm |
| Paper tray 1 input capacity | 250 sheets | Package depth | 379 mm |
| Auto document feeder (ADF) | 1 | Package height | 490 mm |
| Auto document feeder (ADF) input | 50 sheets | Package weight | 13.6 kg |
| capacity Maximum number of input trays | 1 | Packaging content | |
| Maximum input capacity | 250 sheets | Cartridge(s) included | ✓ |
| Maximum output capacity | 150 sheets | Included cartridge capacity (black) | 1000 pages |
| Paper handling | | Cables included | AC |
| Maximum ISO A-series paper size * | Α4 | Warranty card | ✓ |
| Maximum print size | 207 x 348 mm | Logistics data | |
| Paper tray media types * | Cut sheet, Envelopes, Glossy paper, | Harmonized System (HS) code | 8443310000 |
| ISO A-series sizes (A0A9) * | Labels, Plain paper, Postcard A4, A5, A6 | Pallet gross weight | 346.9 g |
| ISO B-series sizes (B0B9) | B5 | Layers per pallet | 4 pc(s) |
| ISO C-series sizes (C0C9) | C5, C6 | Products per pallet | 24 pc(s) |
| Non-ISO print media sizes | Oficio, 16K, L | Technical details | - /> |
| JIS B-series sizes (B0B9) | B6 | Master (outer) cases per pallet layer | 6 pc(s) |
| Envelopes sizes | B5, C5, C6, DL | Other features | |
| Photo paper sizes Custom media width | 10x15 cm 76 - 216 mm | Number of users | 10 user(s) |
| Custom media length | 127 - 356 mm | Pallet dimensions (W $x D x H$) | 1200 x 1000 x 211 mm |
| Paper tray media weight | 60 - 163 g/m ² | Recommended system | Microsoft® Windows® 11, 10, 2 GB available hard disk space, Internet |
| Ports & interfaces | - | requirements | connection, Microsoft® Internet |
| Direct printing * | 1 | Acoustic power emissions (ready) | Explorer or Edge. 32 dB |
| eee p | | , | |

Other features

Acoustic pressure emissions bystander (ready)

14 dB











Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.