



- Supports Nvidia® GeForce RTX™ 50 series graphics cards
- Native 12V-2x6 connector
- Dual-color 12V-2x6 cable
- 80 PLUS Gold certified
- Optimized the sound level
- Main 105°C capacitor
- Embossed Jacket Cables, the cables are more bending and routing
- Industrial level protection with OCP/ OTP/ OPP/ SCP/ OVP/ UVP/ SIP/ NLO

## SPECIFICATIONS

<b>Efficiency Rating</b>	80 PLUS Gold (up to 90%)
<b>Modular</b>	Yes (full modular)
<b>Fan Size</b>	135 mm
<b>Fan Bearing</b>	Fluid Dynamic Bearing
<b>Dimensions (DxWxH)</b>	150 x 150 x 86 mm
<b>PFC Type</b>	Active PFC
<b>Input Voltage Range</b>	100-240V~
<b>Power Watt</b>	850W
<b>Power Excursion</b>	1870W (*up to 220% of the PSU's rated power for 100µs)
<b>Input Frequency Range</b>	47-63 Hz
<b>Protection</b>	OCP/ OTP/ OPP/ SCP/ OVP/ UVP/ SIP/ NLO
<b>ATX (24 pin)</b>	1
<b>EPS (8 pin)</b>	2
<b>PCI-E 5.1 (16 pin)</b>	1 (600W)
<b>PCI-E (6+2 pin)</b>	4
<b>SATA (15 pin)</b>	8
<b>PERIPHERAL (4 pin)</b>	3
<b>FDD (4 pin)</b>	1