

Epson LQ-2090II dot matrix printer 550 cps

Brand : Epson

Article code: C11CF40401

Product name : LQ-2090II

Epson LQ-2090II. Maximum print speed: 550 cps, Character pitch: 10 cpi, Maximum number of copies: 6 copies. Paper tray media types: Envelopes, Continuous paper thickness range: 0,12 - 0,46 mm, Label thickness range: 0,16 - 0,19 mm. Product color: Black, Buffer size: 128 KB, Sound pressure level (printing): 55 dB. Standard interfaces: Parallel, USB 2.0. Print head: 24-pin, Print head life: 400 million characters, Mean time between failures (MTBF): 25000 h



Printing		System requirements	
Maximum printing width (columns) *	136	Server operating systems supported	Windows Server 2003 x64, Windows Server 2008 R2, Windows Server 2012 R2, Windows Server 2016
Colour *	✗	Mac compatibility	✗
Maximum print speed *	550 cps	Weight & dimensions	
Character pitch	10 cpi	Width	612 mm
Maximum number of copies	6 copies	Depth	375 mm
Built-in barcodes	Code 128 (A/B/C), Code 39, EAN13, EAN8, Interleaved 2/5, POSTNET, UPC-A, UPC-E	Height	177 mm
Paper handling		Weight	9.4 kg
Paper tray media types	Envelopes	Packaging data	
Continuous paper thickness range	0.12 - 0.46 mm	Quantity per pack	1 pc(s)
Label thickness range	0.16 - 0.19 mm	Package width	451 mm
Multi-part paper thickness range	0.12 - 0.46 mm	Package depth	735 mm
Single sheet thickness range	0.065 - 0.14 mm	Package height	295 mm
Features		Package weight	12.2 kg
Product colour *	Black	Other features	
Buffer size *	128 KB	Print technology	Dot matrix
Sound pressure level (printing) *	55 dB	Needles	24
Country of origin	Indonesia	Compatible operating systems	
Ports & interfaces		Windows 10, Windows 7, Windows 7, 64-Bit-Version, Windows 8, Windows 8.1, Windows 8.1 x64 Edition, Windows Server 2003 x64, Windows Server 2008 R2, Windows Server 2012 R2, Windows Server 2016, Windows Vista, Windows Vista, 64-Bit-Version, Windows XP, Windows XP Professional x64 Edition SP2 or later	
Standard interfaces *	Parallel, USB 2.0	Technical details	
Endurance		Sustainability certificates	ENERGY STAR
Print head *	24-pin	Logistics data	
Print head life	400 million characters	Products per pallet	14 pc(s)
Mean time between failures (MTBF)	25000 h	Pallet gross weight	0 g
Power		Pallet gross length	120 cm
Power consumption (typical)	49 W	Pallet gross width	80 cm
Power consumption (standby)	49 W	Pallet gross height	4.59 m
Power consumption (economy mode)	49 W		
Operational conditions			
Operating temperature (T-T)	5 - 35 °C		
Operating relative humidity (H-H)	10 - 80%		

System requirements		Logistics data	
Windows operating systems supported	Windows 10, Windows 7, Windows 8, Windows Vista, Windows XP	Products per pallet layer	2 pc(s)
		Products per pallet layer (UK)	3 pc(s)
		Products per pallet (UK)	21 pc(s)
		Pallet weight (UK)	0 g
		Pallet length (UK)	120 cm
		Pallet width (UK)	100 cm
		Pallet height (UK)	4.59 m
		Harmonized System (HS) code	84433210



8715946649870

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 06-DEC-2024. Prints or copies of Information are only valid on the printed Publication date