

Epson DLQ-3500II dot matrix printer 550 cps

Brand : Epson

Article code: C11CH59401

Product name : DLQ-3500II



Epson DLQ-3500II. Maximum print speed: 550 cps, Maximum print speed (draft): 550 cps, Maximum print speed (LQ): 195 cps. Paper tray media types: Envelopes, Continuous paper thickness range: 0,12 - 0,62 mm, Label thickness range: 0,16 - 0,19 mm. Product color: Black, White, Buffer size: 128 KB, Sound pressure level (printing): 59 dB. Standard interfaces: Parallel, USB. Print head: 24-pin, Print head life: 200 million characters, Print yield: 9000000 characters

Printing		Power	
Maximum printing width (columns) *	136	Power consumption (standby)	0.8 W
Maximum print speed *	550 cps	AC input voltage	100-240 V
Maximum print speed (draft)	550 cps	AC input frequency	50 - 60 Hz
Maximum print speed (LQ)	195 cps	Operational conditions	
Character pitch	10 cpi	Operating temperature (T-T)	5 - 35 °C
Maximum number of copies	7 copies	Operating relative humidity (H-H)	10 - 80%
Built-in barcodes	Code 128 (A/B/C), Code 39, EAN13, EAN8, Interleaved 2/5, POSTNET, UPC-A, UPC-E	System requirements	
Character sets	ISO 8859-15, Italic, PC437, PC850, PC858, PC864, Roman 8	Windows operating systems supported	Windows 10, Windows 7, Windows 8, Windows XP
Paper handling		Bundled software	Epson Status Monitor
Paper tray media types	Envelopes	Weight & dimensions	
Continuous paper thickness range	0.12 - 0.62 mm	Width	661 mm
Label thickness range	0.16 - 0.19 mm	Depth	433 mm
Multi-part paper thickness range	0.12 - 0.62 mm	Height	276 mm
Single sheet thickness range	0.065 - 0.19 mm	Weight	18.9 kg
Features		Packaging data	
Product colour *	Black, White	Quantity per pack	1 pc(s)
Buffer size *	128 KB	Package width	430 mm
Sound pressure level (printing) *	59 dB	Package depth	795 mm
Country of origin	Indonesia	Package height	520 mm
Ports & interfaces		Package weight	22.4 kg
Standard interfaces *	Parallel, USB	Other features	
Endurance		Print technology	Dot matrix
Print head *	24-pin	Internal memory	128 MB
Print head life	200 million characters	Needles	24
Print yield	9000000 characters	Compatible operating systems	Windows 10, Windows 7, Windows 8, Windows XP
Mean time between failures (MTBF)	10000 h	Logistics data	
Power		Products per pallet	8 pc(s)
Power consumption (typical)	78 W	Pallet gross weight	0 g
		Products per pallet (UK)	8 pc(s)
		Pallet weight (UK)	0 g
		Harmonized System (HS) code	84433210



8715946668628

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 06-DEC-2024. Prints or copies of Information are only valid on the printed Publication date