

## DELL PowerEdge T360 server 2 TB Tower (4.5U) Intel Xeon E E-2414 2,6 GHz 16 GB DDR5-SDRAM 700 W

**Brand :** DELL **Product family:** PowerEdge **Article code:** EMEA\_PET360SPL1

**Product name:** T360

DELL PowerEdge T360. Processor family: Intel Xeon E, Processor frequency: 2,6 GHz, Processor model: E-2414. Internal memory: 16 GB, Internal memory type: DDR5-SDRAM, Memory layout (slots x size): 1 x 16 GB. Total storage capacity: 2 TB, HDD size: 3.5". Ethernet LAN, Cabling technology: 10/100/1000Base-T(X). Power supply: 700 W, Redundant power supply (RPS) support. Chassis type: Tower (4.5U)





Processor		Design	
Processor manufacturer * Intel Processor family * Intel Xeon E	Product colour Bezel	Black ✓	
	Processor model * E-2414  Processor frequency * 2.6 GHz  Processor boost frequency 4.5 GHz  Performance cores 4	Performance	
		Remote administration	iDRAC9 Basic
Performance cores		Software	
Processor cores	4 12 MD	Operating system installed *	x
Number of processors installed Thermal Design Power (TDP) Processor threads	hermal Design Power (TDP) 55 W	Compatible operating systems *	Canonical Ubuntu Server LTS Microsoft Windows Server with Hyper-V Red Hat Enterprise Linux SUSE Linux Enterprise Server VMware ESXi
Memory		Power	
Internal memory * Internal memory type *	16 GB DDR5-SDRAM	Redundant power supply (RPS) support *	✓
Buffered memory type	Unregistered (unbuffered)	Power supply *	700 W
Memory slots ECC	4x DIMM ✓	Number of redundant power supplies supported	2
Memory clock speed	4800 MHz	Number of redundant power supplies installed	2
Memory layout (slots x size)  Maximum internal memory *	1 x 16 GB 128 GB	Power cable length	2 m
,	120 05	Power cable connector 1	C13 coupler
Storage Total storage capacity *	2 TB	Power cable connector 2  Power cable current	C14 coupler 10 A
Number of HDDs installed	1	Operational conditions	10 A
HDD capacity HDD speed HDD size RAID support * Supported RAID controllers	2 TB 7200 RPM 3.5"  ✓ PERC H355	Storage temperature (T-T) Storage relative humidity (H-H) Operating altitude Non-operating altitude	-40 - 65 °C 5 - 95% 0 - 2048 m 0 - 12000 m

Storage		Carbon footprint	
Hot-Plug support	<b>✓</b>	Total carbon footprint (kg of CO2e)	1409
Optical drive type * Internal drive bays	<b>x</b> 8	Total carbon emissions, standard deviation (kg of CO2e)	1213
Graphics	0	Carbon emissions, manufacturing (kg of CO2e)	296
On-board graphics card	×	Carbon emissions, logistics (kg of CO2e)	155
Network	Dana dana 5720	Carbon emissions, energy usage (kg of CO2e)	930
LAN controller Ethernet LAN	Broadcom 5720 ✓	Carbon emissions, end-of-life (kg of CO2e)	28
Cabling technology Ethernet interface type	10/100/1000Base-T(X) Gigabit Ethernet	Total carbon emissions, w/o use phase (kg of CO2e)	479
Ports & interfaces	_	PAIA version	1.4.0, 2024
Ethernet LAN (RJ-45) ports *	2	Weight & dimensions	
USB 2.0 ports quantity	5	Width	175 mm
USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity	2	Depth Height	581.1 mm 369.5 mm
VGA (D-Sub) ports quantity	1	Technical details	
Serial ports quantity	1	Supported storage drives form	
Expansion slots		factor (internal)	3.5"
PCI Express x4 slots	2		
Design			
Chassis type *	Tower (4.5U)		

