

Epson EB-2250U data projector Standard throw projector 5000 ANSI lumens 3LCD WUXGA (1920x1200) White

Brand : Epson

Article code: V11H871040

Product name : EB-2250U



Epson EB-2250U. Projector brightness: 5000 ANSI lumens, Projection technology: 3LCD, Projector native resolution: WUXGA (1920x1200). Light source type: Lamp, Service life of light source: 5000 h, Service life of light source (economic mode): 10000 h. Focus: Manual, Focal length range: 23 - 38.4 mm, Aperture range (F-F): 1.5 - 2. Video processing: 10 bit, Color modes (2D): Cinema, Dynamic, Video color modes: Dynamic, Cinema, Presentation, sRGB, Blackboard, DICOM simulation mode. Serial interface type: RS-232C

| Projector | | Features | |
|--|--|-----------------------------------|--------------------------|
| Screen size compatibility * | 1270 - 7620 mm (50 - 300") | Noise level (economic mode) | 29 dB |
| Projection distance | 1.5 - 9 m | Noise level * | 39 dB |
| Projection distance (wide) | 0 - 1.5 m | Country of origin | Philippines |
| Projection distance (tele) | 0 - 9 m | Password protection | ✓ |
| Contrast ratio (dynamic) | 15000:1 | Multimedia | |
| Projector brightness * | 5000 ANSI lumens | Built-in speaker(s) * | ✓ |
| Projection technology * | 3LCD | RMS rated power | 16 W |
| Projector native resolution * | WUXGA (1920x1200) | Design | |
| Contrast ratio (typical) * | 15000:1 | Product type * | Standard throw projector |
| Native aspect ratio * | 16:10 | Product colour * | White |
| Number of colours | 1.07 billion colours | Placement | Ceiling, Desktop |
| Projector brightness (economic mode) | 3800 ANSI lumens | Cable lock slot | ✓ |
| Vertical scan range | 200 - 240 Hz | Cable lock slot type | Kensington |
| Keystone correction, horizontal | -20 - 20° | Display | |
| Keystone correction, vertical | -30 - 30° | Built-in display * | ✗ |
| Matrix size | 1.93 cm (0.76") | Power | |
| Matrix type | 3-panel (p-Si TFT active) | Power source * | AC |
| Light source | | Power consumption (typical) * | 405 W |
| Light source type * | Lamp | Power consumption (standby) * | 0.5 W |
| Service life of light source * | 5000 h | Power consumption (economy mode) | 323 W |
| Service life of light source (economic mode) | 10000 h | AC input voltage | 220-240 V |
| Lamp power | 300 W | AC input frequency | 50 - 60 Hz |
| Lamps quantity | 1 lamp(s) | Operational conditions | |
| Lens system | | Operating temperature (T-T) | 5 - 40 °C |
| Focus * | Manual | Storage temperature (T-T) | -10 - 60 °C |
| Focal length range | 23 - 38.4 mm | Operating relative humidity (H-H) | 20 - 80% |
| Aperture range (F-F) | 1.5 - 2 | Storage relative humidity (H-H) | 10 - 90% |
| Zoom type | Manual | Weight & dimensions | |
| Zoom ratio | 1.6:1 | Width | 377 mm |
| Digital zoom | 1.6x | Depth | 291 mm |
| Throw ratio | 1.38 - 2.28:1 | Height | 110 mm |
| Video | | Weight * | 4.6 kg |
| Full HD * | ✓ | Package width | 383 mm |
| 3D * | ✗ | Package depth | 530 mm |
| Video processing | 10 bit | Package height | 210 mm |
| Colour modes (2D) | Cinema, Dynamic | Package weight | 6.4 kg |
| Video colour modes | Dynamic, Cinema, Presentation, sRGB, Blackboard, DICOM simulation mode | Packaging content | |
| | | Remote control included * | ✓ |

| Ports & interfaces | | Packaging content | |
|------------------------------------|--------------------|--------------------------------|--|
| USB 2.0 ports quantity | 2 | Batteries included | ✓ |
| USB 2.0 Type-B ports quantity | 1 | Cables included | AC, HDMI |
| Serial interface type * | RS-232C | Manual | ✓ |
| PC Audio in | ✓ | Bundled software | EasyMP Monitor, EasyMP Multi PC Projection |
| PC Audio out | ✓ | | |
| VGA (D-Sub) ports quantity * | 3 | Technical details | |
| HDMI ports quantity * | 2 | Sustainability certificates | TCO |
| Composite video in * | 1 | Logistics data | |
| Component video (YPbPr/YCbCr) in * | 3 | Quantity per pack | 1 pc(s) |
| DVI port * | ✗ | Products per pallet | 40 pc(s) |
| Mobile High-Definition Link (MHL) | ✓ | Pallet gross weight | 0 g |
| AC (power) in | ✓ | Pallet gross length | 120 cm |
| Network | | Pallet gross width | 80 cm |
| Ethernet LAN * | ✓ | Pallet gross height | 3.5 m |
| Ethernet LAN (RJ-45) ports | 1 | Products per pallet layer | 4 pc(s) |
| Ethernet LAN data rates | 10,100,1000 Mbit/s | Products per pallet layer (UK) | 5 pc(s) |
| Wi-Fi * | ✗ | Products per pallet (UK) | 50 pc(s) |
| Storage | | Pallet weight (UK) | 0 g |
| Card reader integrated * | ✗ | Pallet length (UK) | 120 cm |
| | | Pallet width (UK) | 100 cm |
| | | Pallet height (UK) | 3.5 m |
| | | Harmonized System (HS) code | 85286200 |
| | | Other features | |
| | | RS-232 ports | 1 |
| | | RS-232C | ✓ |



8715946628646



4058154162460

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 31-DEC-2024. Prints or copies of Information are only valid on the printed Publication date